BUCCHI
**Bucchi s.r.l.** via Bonsi, 57 | 48022 Lugo, Ravenna (RA) Italy
T. 0039 0545 901001 | F. 0039 0545 32232 / 212385
www.bucchi.it | info@bucchi.it

dal 1973

# REDUCING SOCKET

## Fittings with GAS threading

Fittings



MODEL CODE: 0400232

## TECHNICAL DATA SHEET

| | |
|---|---|
| Connectivity standard: | Internal thread GAS cylindrical ISO 228/1. |
| Material: | Polypropylene (PP) |
| Color: | Black (RAL 9011) |
| Operating pressure: | 10 bar at 20°C |
| Max working temperature: | 80°C |

### Torques

| Filettature - *Threads - Filetts* | 1/4” | 3/8” | 1/2” | 3/4” | 1” | 1”1/4 | 1”1/2 | 2” |
|---|---|---|---|---|---|---|---|---|
| Serraggio Max materiale PP - *Max Tightening PP material - Serrage Max Matériel PP* | 2 Nm | 3 Nm | 6 Nm | 8 Nm | 10 Nm | 15 Nm | 20 Nm | 25 Nm |
| Serraggio Max materiale PA - *Max Tightening PA material - Serrage Max Matériel PA* | 3 Nm | 5 Nm | 8 Nm | 10 Nm | 12 Nm | 17 Nm | 30 Nm | 35 Nm |


The maximum tightening torques specified for fittings Bucchi depend on the compliance of the threads that reference to international specifications on the threads.

**Bucchi s.r.l.** via Bonsi, 57 | 48022 Lugo, Ravenna (RA) Italy
T. 0039 0545 901001 | F. 0039 0545 32232 / 212385
www.bucchi.it | info@bucchi.it

dal 1973

# REDUCING SOCKET with female-female threaded ends G-G(1)

4000 - Outdoor & Gardening




## Dimensions

| Code | G | G(1) | L(1) | L(2) | H | E | E1 | K |
|---|---|---|---|---|---|---|---|---|
| 0400232.050503 | 3/4" | 1/2" | 19,5 | 16,5 | 38 | 36 | 30 | 36 |
| 0400232.050705 | 1" | 3/4" | 22 | 21 | 46 | 43,5 | 35,5 | 44 |
| 0400232.050907 | 1"1/4 | 1" | 20 | 15 | 44 | 51 | 44 | 52 |
| 0400232.051107 | 1"1/2 | 1" | 20 | 15 | 42 | 60,5 | 44 | 61 |
| 0400232.051109 | 1"1/2 | 1"1/4 | 23 | 23 | 55 | 62 | 56 | 57 |
| 0400232.051511 | 2" | 1"1/2 | 23 | 20 | 50 | 75,5 | 60,5 | 76 |